

Z650

 Kawasaki





Colours available: Candy Super Red, Candy Emerald Green

Z650-B1 SPECIFICATIONS

PERFORMANCE

Maximum horsepower	64 hp/8,500 rpm
Maximum torque	5.8 kg-m/7,000 rpm (41.9 ft-lb/7,000 rpm)
Acceleration	SS 400 m (1/4 mile): 12.4 sec.
Climbing ability	30°
Minimum turning radius	2.4 m (94.5 in.)

ENGINE

Type	4-stroke, 4-cylinder, in-line, transversely mounted, air-cooled, DOHC
------	-----------------------------------------------------------------------------

Displacement	652 cc [39.77 cu. in.]
Bore and stroke	62 x 54 mm (2.44 x 2.13 in.)
Compression ratio	9.5 : 1

Ignition system	Battery and coil
Starting system	Electric starter and kick
Lubrication system	Forced lubrication (wet sump)

TRANSMISSION

Type	5-speed, constant mesh, return shift
Shift pattern	1-N-2-3-4-5
Clutch	Wet, multi-disc

The specifications mentioned here apply to and have been achieved by production models under standard operating conditions. We intend only to give a fair description of the motorcycles and their performance capabilities but these specifications may

FRAME

Type	Tubular, double cradle
Suspension: Front	Telescopic fork
Rear	Swing arm
Tyre size: Front	3.25H—19 4PR
Rear	4.00H—18 4PR

BRAKES

Front	Single disc brake, Effective disc dia. 245 mm (9.646 in.)
Rear	Drum, 180 x 40 mm (7.087 x 1.575 in.)
Braking distance	12 m @ 50 kph (39.4 ft @ 31.1 mph)

DIMENSIONS

Length, overall	2,170 mm (85.4 in.)
Width, overall	850 mm (33.5 in.)
Height, overall	1,145 mm (45.1 in.)
Wheelbase	1,420 mm (55.9 in.)
Ground clearance	145 mm (5.7 in.)
Dry weight	211 kg (465 lbs.)
Fuel tank capacity	16.8 litres (3.7 imp. gal.)

not apply to every machine supplied for sale. Kawasaki Heavy Industries, Ltd. reserves the right to alter specifications without prior notice.



KAWASAKI
HEAVY INDUSTRIES, LTD.
ENGINE AND MOTORCYCLE GROUP

Use your head. Wear a helmet. Enjoy safe riding.

99980-018-04 Printed in Japan